





# tiptel.comPact 42/82 IP 8

## PBX phone systems for modern communications

### Interfaces/Connections

- 2 S<sub>0</sub> ports for up to 2 ISDN trunks/lines\*
- 2 external analogue trunks (FXO)
- 10 SIP accounts with up to 4 simultaneous calls
- 8 analogue ports with caller ID
- 1 LAN interface
- Support of ISDN, point to multipoint and point to point, also mixed

### Terminals

- 4 ISDN phones or 2 digital 4-wire phones\*
- 4 (8) analogue terminals (phone, fax)
- 8 IP phones (also remote via WAN)

### Voice mail system

- 6 hours total capacity
- 48 individual voice mailboxes with 9 individual messages each
- Message transfer per voice information, SMS, single call (missed call)
- 6 different day or night profiles change of messages manually or time-controlled
- 4 auto attendants (welcoming callers and connecting them on demand with one of nine destinations)
- 2 automatic call distribution systems (messages welcoming callers and connecting them with a fixed terminal, queue music)
- 2 information switchboards (welcoming caller and guiding him through the call distribution system))

### Features of the phone system

- Team functions in connection with the phones tiptel 83 System and tiptel 85 System
- Phone book for 5,000 names/numbers
- Integrated Least-Cost-Router
- Configurable call-filter
- TAPI driver for 3rd-party-CTI per LAN
- Switching between 2 voice-channels/connecting over the 2nd voice channel
- Three-party conference, also with external subscribers
- Call diversion internal/external
- Pick-up function
- Follow-me function (for call diversion)
- Automatic CO-line access
- Call-through
- Call-back

### Automatic Call Distribution (ACD)

- Definition of call groups, internal and external members
- Dynamic and static groups configurable (log-in and log-out of subscribers possible)
- Different criteria for call diversion adjustable (simultaneous, load-dependant, interval-dependant, linear without timeout, linear with timeout, busy on busy)
- Activation or switching of groups, manually or time-controlled
- Different central phones for each group configurable (for example answering machine)

### ISDN features

- Call forwarding (automatically, busy (CFB), on no reply)
- Call number suppression
- Three-party conference, switching between lines, hold, consultation call
- Callback on busy, callback on no reply

### Configuration

- Web-based configuration, compatible with all existing operating systems (Windows, MAC, OS etc.) no configuration software necessary
- Plug & Play

### Digital phones supported

- tiptel 83 System S<sub>0</sub>
- tiptel 85 System S<sub>0</sub>
- tiptel 83 VoIP

### Dimensions, Weight

- 260 x 240 x 50 mm (W x H x D)
- Approximately 1,3 kg

### Model

tiptel.comPact 42 IP 8  
tiptel.comPact 82 IP 8

### Article No.

1041133 (INT)  
1041135 (INT)

Subject to modifications | 02/2010

\* The complete PBX phone solutions come with 2 S<sub>0</sub> ports, which can be configured each either external (for an ISDN connection) or internal (to be connected with up to 2 ISDN phones or 1 digital phone)